



JIC/37° Female Swivel (cont)

| PART | | HOSE SIZE INFO | | DIMENSIONS | | | | | | | |
|-----------------------------|-------------------|----------------|-----------|------------|------|------|------|------|------|-------|-------|
| 1 Z part # | 2 327E part # | Thd. | Hose size | A | | D | | EØ | | 1 | 2 |
| | | in | | mm | in | mm | in | mm | in | in | in |
| 10Z-608 | | 3/4-16 | -10 | 67,3 | 2.65 | 38,1 | 1.50 | 9,9 | 0.39 | 7/8 | 15/16 |
| 10Z-610 | 32710E-610 | 7/8-14 | -10 | 70,4 | 2.77 | 40,9 | 1.61 | 12,7 | 0.50 | 1 | 15/16 |
| 10ZR-610^a | | 7/8-14 | -10 | 70,4 | 2.77 | 40,9 | 1.61 | 12,7 | 0.50 | 1 | 15/16 |
| 10Z-612^a | | 11/16-12 | -10 | 69,1 | 2.72 | 39,9 | 1.57 | 12,7 | 0.50 | 11/4 | 1 |
| 12Z-608 | | 3/4-16 | -12 | 66,0 | 2.60 | 38,8 | 1.53 | 9,9 | 0.39 | 7/8 | 1-1/8 |
| 12Z-610 | | 7/8-14 | -12 | 71,4 | 2.81 | 41,4 | 1.63 | 12,2 | 0.48 | 1 | 1-1/8 |
| 12Z-612^a | 32712E-612 | 11/16-12 | -12 | 72,1 | 2.84 | 41,9 | 1.65 | 15,5 | 0.61 | 1-1/4 | 1-1/8 |
| 12ZR-612^a | | 11/16-12 | -12 | 72,1 | 2.84 | 41,9 | 1.65 | 15,5 | 0.61 | 1-1/4 | 1-1/8 |
| 12Z-614^a | | 13/16-12 | -12 | 72,1 | 41,4 | 41,9 | 1.65 | 15,5 | 0.61 | 1-3/8 | 1-1/8 |
| 12Z-616^a | | 15/16-12 | -12 | 73,9 | 2.91 | 43,7 | 1.72 | 15,5 | 0.61 | 1-1/2 | 1-1/4 |
| 16Z-612 | | 11/16-12 | -16 | 80,0 | 3.15 | 45,7 | 1.80 | 15,5 | 0.61 | 1-1/4 | 1-3/8 |
| 16Z-614 | | 1 3/16-12 | -16 | 80,0 | 3.15 | 46,5 | 1.83 | 20,6 | 0.81 | 1-3/8 | 1-3/8 |
| 16Z-616^a | | 15/16-12 | -16 | 83,6 | 3.29 | 49,0 | 1.93 | 20,6 | 0.81 | 1-1/2 | 1-3/8 |
| 16ZR-616 | | 15/16-12 | -16 | 83,6 | 3.29 | 49,0 | 1.93 | 20,6 | 0.81 | 1-1/2 | 1-3/8 |
| 16Z-620^a | | 15/8-12 | -16 | 80,5 | 3.17 | 46,0 | 1.81 | 20,6 | 0.81 | 2 | - |
| 20Z-616 | | 15/16-12 | -20 | 87,9 | 3.46 | 43,9 | 1.73 | 21,6 | 0.85 | 1-1/2 | - |
| 20Z-620 | | 15/8-12 | -20 | 91,7 | 3.61 | 47,8 | 1.88 | 26,7 | 1.05 | 2 | - |
| 24Z-624 | | 17/8-12 | -24 | 99,1 | 3.90 | 52,6 | 2.07 | 32,0 | 1.26 | 2-1/4 | - |
| 32Z-63^a | | 21/2-12 | -32 | 110,2 | 4.34 | 60,7 | 2.39 | 44,5 | 1.75 | 2-7/8 | - |

^a Swivel nuts are universal – both SAE 37° and 45° connections.