



Male straight thread O-ring rigid

PART 1 Z part #	HOSE SIZE INFO		DIMENSIONS						
	Thd.	Hose size	A		D		EØ		1
	in		mm	in	mm	in	mm	in	in
04Z-P04	7/16-20	-04	46,7	1.84	23,4	0.92	4,3	0.17	9/16
04Z-P05	1/2-20	-04	46,7	1.84	23,4	0.92	4,3	0.17	5/8
04Z-P06	9/16-18	-04	45,2	1.78	21,8	0.86	4,3	0.17	11/16
06Z-P06	9/16-18	-06	50,8	2.00	25,4	1.00	6,6	0.26	11/16
06Z-P08	3/4-16	-06	50,0	1.97	24,9	0.98	6,6	0.26	7/8
06Z-P10	7/8-14	-06	47,8	1.88	26,7	1.05	6,6	0.26	1
08Z-P08	3/4-16	-08	59,9	2.36	30,2	1.19	9,7	0.38	7/8
08Z-P10	7/8-14	-08	57,4	2.26	27,7	1.09	9,7	0.38	1
08Z-P12	11/16-12	-08	60,7	2.39	31,0	1.22	9,7	0.38	11/4
10Z-P08	3/4-16	-10	56,1	2.21	30,2	1.19	12,7	0.50	15/16
10Z-P10	7/8-14	-10	59,4	2.34	33,5	1.32	12,7	0.50	1
10Z-P12	11/16-12	-10	60,7	2.39	31,2	1.23	12,7	0.50	11/4
12Z-P10	7/8-14	-12	64,3	2.53	37,1	1.46	12,2	0.48	11/8
12Z-P12	11/16-12	-12	62,0	2.44	31,8	1.25	15,5	0.61	11/4
12Z-P16	15/16-12	-12	65,0	2.56	34,8	1.37	15,5	0.61	11/2
16Z-P16	15/16-12	-16	69,6	2.74	35,3	1.39	20,8	0.82	11/2
20Z-P20	15/8-12	-20	92,2	3.63	48,3	1.90	26,7	1.05	17/8
24Z-P24	17/8-12	-24	92,2	3.63	46,0	1.81	32,0	1.26	21/8

Does not include O-ring. See page 231 O-ring part number.